



CX-92S SERIES: DOUBLE DOOR MAGNETIC LOCKS

CX-92S Series (600 Lbs. & 1200 Lbs.) double door magnetic locks offer the best performance and value. The wide selection of models includes a 'TDS' option with an adjustable timer, lock sensor, door status switch and LED. CX-92 Series magnetic locks are supported with a range of lock mounting accessories, including kits for glass doors. Now UL 1034, UL 294, & ULC S533 listed, and are available in an aluminum or black finish.



Features	
<ul style="list-style-type: none"> • 600 and 1,200 Lbs. single door models • Weather and vandal resistant construction proven over thousands of installations • Compatible with all access/egress systems • Metal mounting jig included • Locking mounting bolts 	<ul style="list-style-type: none"> • Field selectable 12/24 VDC operation • On board MOV power surge protection prevents damage to mag lock • Wide range of mounting brackets and spacers available • Lifetime warranty

MODELS		List Price
600 Lbs.		
CX-92S-06	600 Lbs. Surface Mount Double Door Mag Lock - Basic	\$440.00
CX-92S-06TDS	600 Lbs. Surface Mount Double Door Mag Lock - With Adjustable Timer, Door Status Switch, Lock Sensor, Relay & LED	\$560.00
NEW CX-92S-06-BK	600 Lbs. Surface Mount Single Door - Basic, All-black Finish	\$480.00
NEW CX-92S-06TDS-BK	600 Lbs. Surface Mount Double Door Mag Lock - With Adjustable Timer, Door Status Switch, Lock Sensor, Relay & LED, All-black Finish	\$600.00
1200 Lbs.		
CX-92S-12*	1,200 Lbs. Surface Mount Double Door Mag Lock - Basic	\$520.00
CX-92S-12TDS*	1,200 Lbs. Surface Mount Double Door Mag Lock - With Adjustable Timer, Door Status Switch, Lock Sensor, Relay & LED	\$640.00
NEW CX-92S-12-BK	1,200 Lbs. Surface Mount Double Door Mag Lock - Basic, All-black Finish	\$575.00
NEW CX-92S-12TDS-BK	1,200 Lbs. Surface Mount Double Door Mag Lock - With Adjustable Timer, Door Status Switch, Lock Sensor, Relay & LED, All-black Finish	\$695.00

Specifications

Voltage:	12/24 VDC
Current Draw:	CX-92S-06 TDS: 2 x 510mA @ 12 VDC 2 x 285mA @ 24 VDC CX-92S-12 TDS: 2 x 500mA @ 12 VDC 2 x 265mA @ 24 VDC
Temp Range:	32°F - 131°F (0°C to 55°C)
Contact Rating:	TDS Models Only Bond Sensor: 2A @ 24 VDC Door Status Switch: 0.5A @ 28V AC/DC
Time Delay:	TDS Models Only: 5 - 25 seconds
Static Strength:	CX-92S-06 TDS: 2 x 600 lbs. (Factory Tested) 2 x 500 lbs. (UL Verified) CX-92S-12 TDS: 2 x 1,200 lbs. (Factory Tested) 2 x 1000 lbs. (UL Verified)
Dynamic Strength:	CX-92S-06 TDS: 50 ft-lb x 2 CX-92S-12 TDS: 70 ft-lb x 2
Endurance:	250,000 Cycles
Body Dimensions:	CX-92S-06 TDS & CX-92S-06 TDS-BK: 19-3/4"W x 2"H x 1-1/8"D (500mm x 50mm x 29mm) CX-92S-12 TDS & CX-92S-12 TDS-BK: 21"W x 3"H x 1-9/16"D (532mm x 76mm x 39mm)
Armature Plate:	CX-92S-06 TDS: 2 x 7-5/32"W x 1-3/4"H x 15/32"D 2 x (182mm x 44mm x 12mm) CX-92S-12 TDS: 2 x 7-15/16"W x 3"H x 5/8"D 2 x (202mm x 76mm x 16.5mm)



CX-92S-06



CX-92S-12-BK

